⊣ NEWS RELEASE ⊣

December, 2017

## HSC launches new crawler crane "SCX800E"!

Hitachi Sumitomo Heavy Industries Construction Crane Co., Ltd., (HSC) is pleased to announce the launch of "SCX800E", 80-tonne capacity hydraulic crawler crane. The SCX800E is the third model of the SCX E-series followed by SCX550E and SCX700E.

The crane has a superb, powerful lifting performance with time-tasted components and simple hydraulic and electrical systems with low-maintenance. The SCX800E is a crawler crane model with true high-performance, committed solely to "lifting".

## <FEATURES>

- 1. A good workability and operability Employing an outstanding, simplified winch system with integrated reduction gear(free-fall function included as standard) ensures operability and workability.
- 2. A superior safety and high maintenance ability

For better safety, the crane comes standard with an anti-two block, and a secondary boom hoist limiting device. An automatic drum lock included as standard on the boom hoist winch automatically locks and releases the drum depending on the operation and helps to prevent unexpected accidents. Ultimate reliability is offered by using proven simple hydraulic and electric circuitry. A centralized layout for various filters, fuses and relays minimizes downtime and ensures low-maintenance.

 A super comfortable operation design 1040mm-wide cab and large window delivers comfortable work environment. Furthermore, operator's sheet with superb visibility improves safety during operations or traveling and ensures work efficiency. Full auto air-conditioner is standardized, with heater and cooler box, uses substitute chlorofluorocarbon.

## <SPECIFICATION>

| SCX800E               |                      | Liftcrane                                     |
|-----------------------|----------------------|---|
| Max. lifting capacity |                      | 80t×3.2m                                      |
| Basic boom length     |                      | 9.5.m   |
| Max. boom length      |                      | 54.5m   |
| Rope line             | Front and rear winch | 75 m /min                                     |
| speeds                | Boom hoist winch     | 62 m /min                                     |
| Swing speed           |                      | 3.0 min <sup>-1</sup>                         |
| Engine make and model |                      | ISUZU 6HK1 (Stage II, Tier 2)                 |
| Engine rated output   |                      | 140kW/2,000min <sup>-1</sup> (190PS/2,000rpm) |



\*Photo may differ to the specifications of available products.

\*The contents of the article are as of the date of release and are subject to change without notice.

Hitachi Sumitomo Heavy Industries Construction Crane Co.,Ltd.

9-3, Higashi-Ueno 6-chome, Taito-ku, Tokyo 110-0015, Japan

Phone:81-3-3845-1396 Facsimile: 81-3-3845-1394 http://www.hsc-crane.com